

BE SERIES

COLD WATER PRESSURE WASHER

Belt Drive • Electric Powered • Industrial Cart

- **Oversized On/Off Switch:**
Includes indicator light.
- **Time Delay Shutdown:**
Automatically shuts down the motor when not in use.
- **Baldor TEFC Motor:**
Low speed induction motor extends the life of your pump.
- **Separate Unloader with Pressure Switch:**
Diverts water pressure when trigger is not in use.
- **Downstream Adjustable Chemical Injector:**
For low pressure soap and chemical injection.
- **Inlet Filter:**
Helps reduce contaminants from entering the pump.
- **Chemical Basket:**
For easy chemical storage.



- **Heavy Duty Cart:**
With powder coated finish.
- **Four Quick Connect Nozzles:**
Colour coded nozzles mounted on lance are 0°, 15°, 25° and soap.
- **50' High Pressure Hose:**
Durable non-marking steel braided hose.
- **Quality Gun and Dual Stainless Steel Lance Combination:**
For easy dial in soap injection.
- **High Quality Triplex Plunger Pump:**
All Dynablast pressure washers include GP/Interpump pumps with solid ceramic plungers, thermal pump protector and limited 5 year warranty.
- **Belt Drive:**
Slower speed increases the life of the pump.
- **Rubber Foot:**
Reduces vibration.
- **13" Pneumatic Tires:**
Ball bearing construction with a steel rim and hub assembly.

SPECIFICATIONS

ASSEMBLED IN CANADA

MODEL	C4320BE1/3D	C5030BE1/3D
Operating Pressure (PSI):	2000	3000
Volume (GPM):	4.3	5.0
Motor (HP):	6	10
Pump Speed (RPM):	900	1300
Voltage:	230/575	230/575
Amps:	16/7.5	42/11
Dimensions (LxWxH):	34"x25"x39"	34"x25"x39"
Unit Weight:	320 lbs	350 lbs

Other Features:

- CSA Certified
- Heavy Duty Power Cord and Plug
- Lance and Gun Holder



Features and specifications subject to change without prior notice.

Dynablast®



Distributed by:

www.dynablast.com

BE-A-08/06