

DESS SERIES

COLD WATER PRESSURE WASHER

Direct Drive • Electric Powered • Stainless Steel Cart

- **Downstream Adjustable Chemical Injector:**

For low pressure soap and chemical injection.

- **Quick Connect Hose Connectors:**

For easy on/off connections and tangle free hoses.

- **Baldor TEFC Motor:**

Low speed induction motor extends the life of your pump.

- **Separate Unloader:**

Diverts water pressure when trigger is not in use. Includes easily adjustable pressure control knob and all brass fittings.

- **Inlet Filter:**

Helps reduce contaminants from entering the pump.

- **Chemical Basket:**

For easy chemical storage.

- **Heavy Duty Stainless Steel Reversible Cart:**

Includes gun and lance holder.

- **10" Never-Go-Flat Tires**

Ball bearing construction with a steel rim and hub assembly.

- **Four Quick Connect Nozzles:**

Colour coded nozzles included are 0°, 15°, 25° and soap.

- **50' High Pressure Hose:**

Durable non-marking steel braided hose.

- **Quality Gun and Stainless Steel Lance Combination:**

Easy pull trigger with 36" lance.

- **High Quality Triplex Plunger Pump:**

All Dynablast pressure washers include GP/Interpump pumps with solid ceramic plungers, thermal pump protector and limited 5 year warranty.

- **Rubber Foot:**

Reduces vibration.



Other Features:

- Warnock Hersey Certified
- Heavy Duty Power Cord and Plug
- Pressure Gauge
- Stainless Steel Name Plate and Hose Holder

SPECIFICATIONS

ASSEMBLED IN CANADA

MODEL	C2010DESS	C3015DESS	C3621DESS
Operating Pressure (PSI):	1000	1500	2100
Volume (GPM):	2.1	3.0	3.6
Motor (HP):	1.5	3	5
Pump Speed (RPM):	1750	1750	1750
Voltage:	115	230	230
Amps:	13.6	13.2	23
Dimensions - Handle Up (LxWxH):	33"x22"x35"	33"x22"x35"	33"x22"x35"
Dimensions - Handle Down (LxWxH):	40"x22"x28"	40"x22"x28"	40"x22"x28"
Unit Weight:	95 lbs	118 lbs	185 lbs

Features and specifications subject to change without prior notice.



Dynablast®



Distributed by: