

HT SERIES

HOT WATER PRESSURE WASHER

Direct Drive • Electric Powered • Stainless Steel Cart

- **Quick Connect Hose Connectors:**
For easy on/off connections and tangle free hoses.
- **Baldor Electric TEFC Motor.**
- **Thermally Protected Pump:**
Up to 190° F.
- **Rubber Foot:**
Reduces vibration.
- **Flex Coupler:**
For longer pump and motor life.
- **5 Year Warranty:**
All Dynablast pressure washers include a 5 year limited warranty.
- **Heavy Duty Stainless Steel Reversible Cart:**
Including Stainless Steel name plate and hose holder.
- **High Pressure Hose:**
Durable non-marking steel braided hose.
C5004HTSS - 30'
C1904HTSS - 50'
CS1904HTDS - 50'
CS1904HTDS3D - 50'
- **Quality Gun and Lance Combination:**
Easy pull trigger with 36" lance.
- **Separate Unloader:**
Diverts water pressure when trigger is not in use. Includes easily adjustable pressure control knob and all brass fittings.
- **High Quality Interpump HT Series Triplex Plunger Pump:**
HT Series pumps can run hot water up to 185° F.
- **10" Never-Go-Flat Tires:**
Ball bearing construction with a steel rim and hub assembly.



Other Features:

- Brass Y Inlet Strainer
- Gun and Lance Holder

SPECIFICATIONS	ASSEMBLED IN CANADA			
MODEL	C5004HTSS	C1904HTSS	CS1904HTDS	CS1904HTDS3D
Operating Pressure (PSI):	500	1900	1900	1900
Volume (GPM):	4.0	4.0	4.0	4.0
Motor (HP):	1.5	5.0	5.0	5.0
Pump Speed:	1750	1750	1750	1750
Available Voltage (1 Phase):	115	230	230	575 V (3-Phase)
Amps:	13.5	22	22	5.7
Time Delay Shutdown:	No	No	Yes	Yes
Dimensions - Handle Up (LxWxH)	33"x22"x35"	33"x22"x35"	33"x22"x35"	33"x22"x35"
Dimensions - Handle Down (LxWxH)	40"x22"x28"	40"x22"x35"	40"x22"x35"	40"x22"x35"
Unit Weight:	100 lbs	195 lbs	205 lbs	195 lbs

Features and specifications subject to change without prior notice.

Distributed by:

Dynablast®



HT-C-03/10

www.dynablast.com