

HVLS2 SERIES

HOT WATER PRESSURE WASHER

Diesel Fired Heater Module

- **High Limit Switch:**
For added safety
- **Burner Temperature Control:**
Adjust your water temperature with ease.
- **High Pressure Blow-Off Valve:**
For added safety.
- **Compact Design:**
Ideal for tight spaces and stationary applications.
- **Cold Water Quick Connect:**
For easy connection to your cold water pressure washer.
- **Burner ON/OFF Switch**

- **Primary Control (CAD):**
On all burners
- **Welded 7 Gauge Wrapped Steel Base and Leg Supports**
- **Welded Inner Coil for Coil Support**
- **Stainless Steel Target Plates in all Coils**
- **Momentary Test, Flow & Thermostat**
- **HV120DPLS, included with HV700FLS and HV900FLS**
- **HV12DPLS, included with HV690FLS-12V**
- **Removeable Service Access Panel**
- **All Heaters Fuel No. 1 or No. 2**
- **Powder Coated Paint Finish**



HV690FLS-12V

Access Panel



Certified UL1776

ASSEMBLED IN CANADA

SPECIFICATION	NON-STEAM ETL CERTIFIED		
MODEL	HV690FLS-12V	HV700FLS	HV900FLS
Operating Pressure (PSI)	3500	3500	3500
BTU	690,000	700,000	900,000
Heat Rise	7GPM @ 165°F	7GPM @ 170°F	10GPM @ 155°F
Coil	3/4" Schedule 80	3/4" Schedule 80	3/4" Schedule 80
Burner	Beckett SDC 12V	Wayne EH 120V	Beckett CF800 120V
Fuel Consumption	5.06 GPH	5.03 GPH	5.81 GPH
Coil Water Discharge	Bottom	Bottom	Bottom
Dimensions (L x W x H)	26.5" x 26.5" x 58"	26.5" x 26.5" x 58"	26.5" x 26.5" x 64"
weight	780 lbs	780 lbs	880 lbs

Features and specifications subject to change without prior notice.

Dynablast®



Distributed by:

