


Technical Manual



Specifications/Reference

	PWP3SST
Port Size	3" NPT
Seal Material	Silicon Carbide
Impeller Material	Cast Iron
Volute Material	Cast Iron
Pump Casing Material	Aluminum
Suction Lift ft (m)	26 (8)
Max Head ft (m)	76 (23)
Max Flow gpm (lt/min)	264 (1000)
Solids Capacity in (mm)	.8 (20)
Weight lbs (kg)	57 (26)
size inches (mm) LxWxH	20x16x16 (500x400x396)
Engine	Honda GX160
Engine Spec #	K1WKT2
Engine type	4 stroke
oil Alert	Yes
Engine output hp(kw)	5.5(4.1)
Fuel Tank Capacity gal (l)	1(3.8)

Centrifugal Pump Reference Information

Losses due to hose friction

Hose Friction losses					
Pressure Drop in psi per 100 ft of hose with typical flow rates					
Water Flow (gpm)	1"	1.5"	2"	3"	4"
10	7				
20	26				
30	56	8			
40	96	13			
50	144	20	5		
100		72	18		
150		153	38	5	
200			64	8.9	
250			97	14	
300				19	4
350				25	6
400				32	8
450					10
500					12
550					14

Losses are expressed in feet of head loss


Values are based on the Hasen-Williams Equation and are close approximations

Losses due to elevation


Pressure can be designated in many units from bar (si), psi (imperial) or also in high of a water column (feet or metres). In imperial units the weight of one foot of water is equal to .4328 psi. In other words for every foot of elevation change from the discharge of the pump to the point of discharge of the hose there is a pressure of .4328 psi applied to the pump.

1 foot of water (head) = .4328 psi

Pump Curve PWP3SST



Parts Illustration PWP3SST



Parts Illustration PWP3SST

REF No.	Parts No.	Parts name	Q'ty	Remarks
		HONDA GX160	1	
1	803-001	CASING	1	OEL-80
2	501-004	CASING COVER	1	
3	871-009	IMPELLER	1	
4	871-011	INNER CASING	1	
5	801-019A	BEND	1	EX-NPSH3
6	801-013A	VALVE CASE	1	EX-NPSH3
7	521-008	MECHANICAL SEAL	1	2",3"Sic
8	501-002	O-RING	1	W1517-45
9	801-012	PACKING, INNER CASING	1	
10	801-020	PACKING, BEND	1	
11	801-015	CHECK VALVE	1	
12	501-022	O-RING	(2)	P-24
13	-	PLUG ASSY	2	
14	-	CASING BOLT ASSY	4	M8×50
15	571-003	SPECIAL BOLT	4	M10
16		SPRING WASHER	4	M10
17	801-014	HEX.BOLT	3	M8×30 P=3
18	501-014	HEX.BOLT	4	M8×25 P=3
19	501-023	HEX.BOLT	4	M8×40 P=2
20	501-024	FLANGE NUT	4	M8
21	871-030	FRAME(WHITE)	1	
22	801-017	PACKING,COUPLING	2	NBR
23	801-018P	HOSE COUPLING	2	ABS
24	801-016A	COUPLING HANDLE	2	NPSH3
25	571-021	PLATE	1	
26	571-022	WRENCH	1	14×17
27	801-028	HOSE BAND	3	3"
28	875-029	STRAINER	1	3"FJ