



Stopmatic



- 145 psi Max. Pressure
- 4.75 gpm Max. Flow
- 140°F Max. Temperature
- 1/2" BSP-M Inlet
- 1/2" BSP-M Outlet
- 250V, 1.0A
- Total stop in low pressure mode

Product No.	Description
STOPMATIC	Stopmatic Switch

Flow Switch



- 4000 psi Max. Pressure
- 12.0 gpm Max. Flow
- 0.5 gpm Switching Flow
- 108°F Max. Temperature
- 3/8" NPT-F Inlet
- 3/8" NPT-F Outlet

Product No.	Description
GP100879	Flow Switch

103012PV Flow Switch (GP100329)



- 4000 psi Max. Pressure
- 18.7 gpm Max. Flow
- 0.75 gpm Switching Flow
- 195°F Max. Temperature
- 3/8" NPT-F Connections
- 250V, 3.0A
- 40.0 oz Weight

Product No.	Description
103012PV	Flow Switch

FSI Flow Switch



- 3650 psi Max. Pressure
- 8.0 gpm Max. Flow
- 0.8 gpm Switching Flow
- 175°F Max. Temperature
- 3/8" BSP-M Connection
- 230V, 3.0A
- 10.2 oz Weight

Product No.	Description
FSI	FSI Flow Switch
28051823P	Replacement Probe

FL7N Flow Switch



- 5100 psi Max. Pressure
- 8.0 gpm Max. Flow
- 1.06 gpm Switching Flow (Vertical)
- 0.8 gpm Switching Flow (Horizontal)
- 175°F Max. Temperature
- 3/8" BSP-F Connection
- 230V, 3.0A

Product No.	Description
FL7N	FL7 Flow Switch
28051823P	Replacement Probe

FL7MS Flow Switch



- 5100 psi Max. Pressure
- 0.1 gpm Switching Flow
- Highly Sensitive, Min flow rate intervention.
- 15.9 gpm Max. Flow Rate
- 230 volts, 3 amps
- 3/8" BSP-F Connection
- 165°F Max. Temperature

Product No.	Description
FL7MS	Flow Switch

FL7SS Stainless Steel Flow Switch



- 7300 psi Max. Pressure
- 8 gpm Max. flow rate - intake
- 16 gpm Max. flow rate - delivery
- 1.06 gpm Switching Flow (Vertical)
- 0.8 gpm Switching Flow (Horizontal)
- 75°C - 165°F Max. Temperature
- 230V Max. Voltage
- 60 V A Max. switch capacity
- 3 A Max. Curr. Strength
- 1250 mm - 49.2" Cable length
- 3/8" BSP-F Inlet/Outlet

Product No.	Description
FL7SS	Flow Switch

Reedless Inline Flow Switch



- 5.0A Micro Switch
- 0.5 gpm Switching Flow
- 48", 18 AWG lead
- Uses magnets instead of springs
- 180°F Max. Temp
- 3/8" NPT-F Outlet/Outlet
- 250 VAC Voltage

Product No.	Description
GP100934	Brass inline flow switch - 12 gpm/5000 psi
GP100953	SS inline flow switch - 12 gpm/5800 psi

Simplex3 Pressure Switch



- 3000 psi Max. Pressure
- 725 psi Min. Pressure
- 435 psi Switching Pressure
- 21.0 gpm Max. Flow
- 1/4" BSP-M Inlet
- 250V, 1.0A

Product No.	Description
SIMPLEX3	Simplex3 Switch

PSW1-15B Pressure Switch



- 3650 psi
- 220 psi Switching Pressure
- 195°F Max. Temperature
- 250V, 16.0A
- 1/4" BSP-M Connection

Product No.	Description
PSW1-15B	Pressure Switch - 15 bar.

Call or Fax

Phone TOLL FREE: 1.888.881.6667
Fax TOLL FREE: 1.800.350.5666

A54

www.dynablast.ca

Email

dealersales@dynablast.ca