



**FILTRI  
FILTERS**

■ F10

Alluminio  
Aluminium



10 bar  
1 MPa  
145 psi  
100 l/min  
26.4 gpm

200/310 microns

**VALVOLE DI MASSIMA PRESSIONE  
MAX PRESSURE SETTING VALVES**

■ S723

Ottone  
Brass



700 bar  
70 MPa  
10150 psi  
230 l/min  
60.8 gpm

■ SX2

Acciaio inox  
Stainless steel



720 bar  
72 MPa  
10442 psi  
190 l/min  
50 gpm

**REGOLATORI DI PRESSIONE  
REGULATING VALVES**

■ R1

Ottone  
Brass



**R1/200 - R1X/200**  
200 bar  
20 MPa  
2900 psi  
110 l/min  
29 gpm

**R1/400 - R1X/400**  
400 bar  
40 MPa  
5800 psi  
110 l/min  
29 gpm

■ R1X

Acciaio inox  
Stainless steel



**R1/600 - R1X/600**  
600 bar  
60 MPa  
8700 psi  
70 l/min  
18.5 gpm

**VALVOLE AUTOMATICHE  
UNLOADER VALVES**

■ H560



500 bar  
50 MPa  
7250 psi  
60 l/min  
15.8 gpm

■ BKX600



600 bar  
60 MPa  
8700 psi  
60 l/min  
15.8 gpm

**VALVOLE PNEUMATICHE  
PNEUMATICALLY OPERATED VALVES**

■ PN2

Acciaio inox  
Stainless steel



**PN2/140**

140 bar  
14 MPa  
2030 psi  
230 l/min  
61 gpm

**PN2/250**

250 bar  
25 MPa  
3626 psi  
230 l/min  
61 gpm

**PN2/500**

500 bar  
50 MPa  
7250 psi  
230 l/min  
61 gpm

**LANCE COMPLETE  
SPRAY GUNS**

■ P560

Lunghezza 750/1000mm  
Lenght 750/1000mm



600 bar - 60 MPa - 8700 psi  
60 l/min - 15.8 gpm

■ P560/S

Lunghezza 750/1000mm  
Lenght 750/1000mm



600 bar - 60 MPa - 8700 psi  
60 l/min - 15.8 gpm

**UGELLI / NOZZLES**

■ N1



Acciaio inox  
Stainless steel

Max. 300 bar  
Max. 30 MPa  
Max. 4350 psi

**ACCUMULATORI ANTIPULSAZIONI  
PULSATION DAMPENERS**

■ A4X

Volume 0,35 l  
Volume 0,35 l

Acciaio inox  
Stainless steel



Max. 210 bar  
Max. 21 MPa  
Max. 3045 psi

**MANOMETRI  
PRESSURE GAUGES**

■ PG1 ■ PG2



0-120 bar 0-12 MPa  
0-160 bar 0-16 MPa  
0-250 bar 0-25 MPa  
0-400 bar 0-40 MPa  
0-600 bar 0-60 MPa  
0-1000 bar 0-100 MPa

Attacco Gas 1/4"  
Connection Gas 1/4"

**VALVOLE NON RITORNO  
CHECK VALVES**

■ UD1



**UD1/5  
UD1/02**  
250 bar  
25 MPa  
3650 psi  
180 l/min  
48 gpm

Prearica / Load  
5 bar - 0,5 MPa - 72 psi  
0,2 bar - 0,02 MPa - 3 psi

**SLITTE TENDICINGHIE  
SLIDES**

■ TC-G



Per installazioni fino a 50 hp/37 kW  
For installation up to 50 hp/37 kW